

**WHAT IS CLAIMED IS:**

1. A speaker comprising:
    - a T-yoke;
    - 5 a washer;
    - a magnet mounted in between said T-yoke and said washer;
    - a basket provided at a top side of said washer;
    - a voice coil mounted in said basket;
    - a cone mounted in said basket; and
    - 10 a damper mounted in said basket around said voice coil;
- wherein said basket comprises a top flange, a bottom flange, a plurality of screw holes at said top flange, and a plurality of through holes at said bottom flange; said cone has a suspension extended around of the periphery thereof and rested on said top flange of said basket; a gasket is covered on the periphery of said suspension at
- 15 said top flange of said basket, said gasket having a bottom groove capped on a protruded part of said suspension at said basket, and a plurality of mounting through holes respectively fastened to the screw holes at said top flange of said basket by screws; said damper is peripherally mounted on said bottom flange of said basket; a holder frame is fastened to said basket to hold said damper in place, said holder frame
- 20 having a bottom groove capped on the periphery of said damper at said bottom flange of said basket, and a plurality of screw holes respectively fastened to the mounting through holes at said bottom flange of said basket by screws.
2. The speaker as claimed in claim 1, wherein said basket further comprises a first rib disposed at said top flange corresponding to the bottom groove of said gasket
  - 25 and adapted to support the suspension of said cone, and a second rib disposed at said

bottom flange corresponding to the bottom groove of said holder frame and adapted to support the periphery of said damper.